

METAPACE



- Direct thermal transfer printer for professional label applications
- Faster printing at up to 152 mm per second
- Particularly large colour transfer band supply (up to 300 m long)
- Unpack and start printing: PSU, label roll, transfer ribbon and cleaning pen included

Specifications

Printing method	Thermal transfer
Print width	104 mm
Colour	Black, white
Print speed	152 mm/sec
Paper supply method	Easy paper loading
Resolution	8 dots/mm (203dpi)
Character set	7 bitmap fonts, 7 code page, expandable up to 4X, soft font storage BMP, PCX graphics supported
Paper type	Gap, notch, black mark, continuous, fan-fold
Paper roll diameter	130 mm (outer) / 25.4 ~ 38.1 mm (inner)
Reliability	MCBF : 12 months, auto cutter: 6 months, TPH : 6 months
Bar codes	Code 39, Code 93, Code 128, interleave 2 of 5, Coda Bar, UPC-A, UPC-E, EAN-8, EAN-13, Maxicode(2D), QR Code(2D), PDF 417(2D), Data Matrix (2D)
Emulation	SLCS, EPL II, ZPL II, ESC/POS
Drivers	Windows 95/98/ME/2000/NT/XP/2003/VISTA
Sensors	Transmissive sensor, reflective sensor (position adjustable), ribbon-end, head
Receive buffer size	256K Bytes
Interfaces	RS232C, IEEE1284, USB (all standards), Ethernet
Options	Autocutter, manual cutter, wall mount bracket, splash proof cover
Power supply	AC100 ~240V, DC 24V, 3.75A
Dimensions (mm)	214 (W) x 310 (L) x 200 (H)
Warranty	24 months



Unpack & get started
Triple interface integrated

Your Dealer